

Tubo en espiral de poliamida sin enchufe

643 SPIR

Descripción									
Referencia	Peso neto (kg)	Color	Ø de bobinas	Ø exterior (mm)	Ø interior (mm)	Longitud	Longitud Mini	Presión max. de utilización	Temperatura
SPIR 1016	1,02	Azul	144.00 mm	12.00	9.50	17.00 m	0.97 M	10.00 bar	-20.00°C a 90.00°C
SPIR 12730	4	Azul	222.00 mm	16.00	12.70	24.00 m	1.33 M	10.00 bar	-20.00°C a 90.00°C
SPIR 1630	4,773	Azul	230.00 mm	20.00	16.00	20.00 m	1.33 M	10.00 bar	-20.00°C a 90.00°C
SPIR 2710	0,156	Azul	28.00 mm	4.00	2.70	10.00 m	1.06 M	10.00 bar	-20.00°C a 90.00°C
SPIR 4526	0,675	Azul	72.00 mm	6.00	4.00	26.00 m	1.33 M	10.00 bar	-20.00°C a 90.00°C
SPIR 456	0,395	Azul	52.00 mm	6.00	4.50	9.00 m	1.00 M	10.00 bar	-20.00°C a 90.00°C
SPIR 610	0,405	Azul	96.00 mm	8.00	6.00	10.00 m	0.48 M	10.00 bar	-20.00°C a 90.00°C
SPIR 620	0,67	Azul	96.00 mm	8.00	6.00	20.00 m	0.96 M	10.00 bar	-20.00°C a 90.00°C
SPIR 820	0,92	Azul	110.00 mm	10.00	8.00	20.00 m	1.10 M	10.00 bar	-20.00°C a 90.00°C

